

規格 SPECIFICATIONS :

波 長 Wavelength	630 ~ 650 nm (RED)	
輸出功率 Output Power	10 mW / 20 mW / 30 mW / 40 mW / 50 mW	
標線長度 Line Length	4 ~ 6 M / 7 ~ 10 M / 11 ~ 14 M / 15 ~ 18 M / 19 ~ 22 M(INDOOR)	
輸入電壓 Input Voltage	AC 90 ~ 260V to DC 5V Adaptor (PS1) or PS3 or PS5	DC 24V
操作溫度 Operating Temp.	- 10 ~ 50 °C	
安全等級 Safety Class	Class IIIb	
使用壽命 Lifetimes	> 20,000 小時 (hr)	
外觀尺寸 Dimensions	D 25 × L 100 (mm)	
重 量 Weight	80 ± 5 公克 (g)	
適用行業 Applications	<ul style="list-style-type: none"> ● 木材加工 Wood working ● 石材加工 Stone working ● 橡膠加工 Rubber processing ● 鐵材加工 Metal working ● 布料加工 Fabric processing 	
備 註 Remarks	<p>1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質 (如:塑鋼、電木), 以隔絕雷射頭與機械設備的電位接觸。 If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</p> <p>2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源。 Do not catch your sight with the beam. It may result in the harm to your eyes.</p> <p>3. 請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本。 Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.</p>	

應用範例 Example :

